


DATE	SYM	REVISION RECORD	AUTH	DR.	CK.
10/10/14	B	REDRAWN AND UPDATED TO ROHS 2 COMPLIANT	T.B.	B.S.	
03/24/17	C	ADDED DIM. 61.30 DIM. 55.10 WAS 55.00 DIM. 14.50 WAS 15.50	T.B.	B.S.	
04/21/17	D	UPDATED SPECIFICATION	T.B.	B.S.	

SPECIFICATIONS :

Plastic material - polypropylene
 Flammability Rating-UL94 HB, UL File No. E216959
 Temperature Range: -10°C to +100°C
 Springs - nickel plated spring steel
 Rivets - Brass, nickel plated
 Lugs - Brass, nickel plated
 Contact Resistance: Under 50m for +/- contacts per EIA-540J000
 ROHS 2 COMPLIANT

Note: Dimensions in mm. (inches)

Tolerance (Except as noted)	 Memory Protection Devices, Inc 200 Broad Hollow Road, Farmingdale, New York 11735		
decimal ±.5 (.020)		Scale	Drawn By B.S.
Fractional ± .8 (.030)	Title FOUR "AA" CELL HOLDER WITH SOLDER LUGS		
Angular ± 3°	Date 04/21/17	Drawing Number BC4AAL	
		Approved By T.B.	